

Package: GrapheR (via r-universe)

October 21, 2024

Encoding UTF-8

Type Package

Title A Multi-Platform GUI for Drawing Customizable Graphs in R

Version 1.9-86-5

Date 2023-11-06

Author Maxime HERVE

Maintainer Maxime HERVE <maxime.herve@univ-rennes1.fr>

Depends R (>= 2.13.0), tcltk

Description A multi-platform user interface for drawing highly customizable graphs in R. It aims to be a valuable help to quickly draw publishable graphs without any knowledge of R commands. Six kinds of graph are available: histogram, box-and-whisker plot, bar plot, pie chart, curve and scatter plot.

License GPL-2

LazyLoad yes

LazyData true

NeedsCompilation no

Date/Publication 2023-11-06 15:40:09 UTC

Repository <https://maximeherve.r-universe.dev>

RemoteUrl <https://github.com/cran/GrapheR>

RemoteRef HEAD

RemoteSha 99791685e4fffd8f9a994d85557f4d230f3e5323

Contents

GrapheR-package	2
run.GrapheR	3
Swallows	3

Index	4
--------------	----------

GrpheR-package

A Multi-Platform GUI for Drawing Customizable Graphs in R

Description

A multi-platform user interface for drawing highly customizable graphs in R. It aims to be a valuable help to quickly draw publishable graphs without any knowledge of R commands. Six kinds of graph are available: histogram, box-and-whisker plot, bar plot, pie chart, curve and scatter plot.

Details

Package:	GrpheR
Type:	Package
Version:	1.9-86-5
Date:	2023-11-06
License:	GPL-2
LazyLoad:	yes

Author(s)

Maxime HERVE

Maintainer: Maxime HERVE <maxime.herve@univ-rennes1.fr>

References

DALGAARD P (2001) A Primer on the R-Tcl/Tk Package. *R News*, **1(3)**, 27–31.

DALGAARD P (2002) Changes to the R-Tcl/Tk Package. *R News*, **2(3)**, 25–27.

HERVE M (2011) GrpheR: a multiplatform GUI for drawing customizable graphs in R. *The R Journal*, **3(2)**, 45–53.

Examples

```
## Not run:  
# To launch or re-launch the interface after closing:  
run.GrapheR()  
  
## End(Not run)
```

`run.GrapheR`*Run GrapheR*

Description

The function launches GrapheR. Use it after closing the interface to re-launch it.

Usage

```
run.GrapheR(lang = NULL, path.to.save = NULL, figurej = FALSE)
```

Arguments

<code>lang</code>	language, when the interface is relaunched.
<code>path.to.save</code>	if not NULL, code is automatically generated and saved when drawing a graph, without asking any question. The file is created in the given folder.
<code>figurej</code>	if TRUE, allows to choose the "FigureJ" option when saving a graph. This will save the graph (and the associated code) in a format adapted for the pulgin FigureJ of the Software ImageJ.

Author(s)

Maxime HERVE <maxime.herve@univ-rennes1.fr>

`Swallows`*Swallows dataset*

Description

An illustrative and fictive dataset about African and European swallows.

Usage

```
Swallows
```

Format

1. Species
2. Sex
3. Size
4. Weight
5. Coconuts
6. Distance

Index

* **datasets**

Swallows, [3](#)

GrapheR (GrapheR-package), [2](#)

GrapheR-package, [2](#)

run.GrapheR, [3](#)

Swallows, [3](#)